



State of Arkansas  
OFFICE OF STATE PROCUREMENT  
1509 West Seventh Street, Room 300  
Little Rock, Arkansas 72201-4222

## INVITATION FOR BID

IFB Number: <b>SP-17-0022</b>	Buyer: <b>John Leverett</b>
Commodity: <b>Crawler Tractor/Dozers with Bulldozer Blade</b> Agency: <b>Arkansas Agriculture Department (AAD)</b>	Bid Opening Date: <b>September 15, 2016</b>
Date Issued: <b>September 1, 2016</b>	Bid Opening Time: <b>3:00 pm Central Time</b>

BIDS WILL BE ACCEPTED UNTIL THE TIME AND DATE SPECIFIED ABOVE. THE BID ENVELOPE, INCLUDING THE OUTSIDE OF OVERNIGHT PACKAGES, **MUST** BE SEALED AND SHOULD BE PROPERLY MARKED WITH THE BID NUMBER, DATE AND HOUR OF BID OPENING AND VENDOR'S RETURN ADDRESS. IT IS NOT NECESSARY TO RETURN "NO BIDS" TO THE OFFICE OF STATE PROCUREMENT.

Vendors are responsible for delivery of their bid documents to the Office of State Procurement prior to the scheduled time for opening of the particular bid. When appropriate, vendors should consult with delivery providers to determine whether the bid documents will be delivered to the OSP office street address prior to the scheduled time for bid opening. Delivery providers, USPS, UPS, and FedEx deliver mail to our street address on a schedule determined by each individual provider. These providers will deliver to our offices based solely on our street address.

<b>MAILING ADDRESS:</b> Office of State Procurement 1509 West Seventh Street, Room 300 Little Rock, AR 72201-4222  <b>TELEPHONE NUMBER:</b> 501-324-9316	<b>BID OPENING LOCATION:</b> Office of State Procurement 1509 West Seventh Street, Room 300 Little Rock, AR 72201-4222
---	---

Company Name: \_\_\_\_\_

Name (type or print): \_\_\_\_\_ Title: \_\_\_\_\_

Address: \_\_\_\_\_ City: \_\_\_\_\_ State: \_\_\_\_\_ Zip Code: \_\_\_\_\_

Telephone Number: \_\_\_\_\_ Fax Number: \_\_\_\_\_

E-Mail Address: \_\_\_\_\_

Signature: \_\_\_\_\_

**USE INK ONLY. UNSIGNED BIDS WILL NOT BE CONSIDERED**

Business Designation Individual ☐ Sole Proprietorship ☐ Public Service Corp ☐  
(check one):  
Partnership ☐ Corporation ☐ Government/ Nonprofit ☐

STATE OF ARKANSAS  
Invitation For Bid

Bid No: SP-17-0022

Page 2 of 20

TYPE OF CONTRACT:	Firm
CONTRACT PERIOD:	N/A
AGENCY P.R. NUMBER:	1000756620

1. **MINORITY BUSINESS POLICY:** Minority participation is encouraged in this and in all other procurements by state agencies. Minority is defined by Arkansas Code Annotated § 15-4-303 as a lawful permanent resident of this state who is: African American, Hispanic American, American Indian, Asian American, Pacific Islander American or a Service Disabled Veteran as designated by the United States Department of Veterans Affairs. The Arkansas Economic Development Commission conducts a certification process for minority business. Bidders unable to include minority-owned business as subcontractors "may explain the circumstances preventing minority inclusion".

Check minority type:

African American\_\_\_\_  
Asian American\_\_\_\_

Hispanic American\_\_\_\_  
Pacific Islander American\_\_\_\_

American Indian\_\_\_\_  
Service Disabled Veteran\_\_\_\_

Arkansas Minority Certification Number\_\_\_\_\_

2. **EQUAL EMPLOYMENT OPPORTUNITY POLICY:** In compliance with Arkansas Code Annotated § 19-11-104, the Office of State Procurement is required to have a copy of the vendor's Equal Opportunity Policy prior to issuing a contract award. EO Policies may be submitted in electronic format to the following email address: [eeopolicy.osp@dfa.arkansas.gov](mailto:eeopolicy.osp@dfa.arkansas.gov), or as a hard copy accompanying the solicitation response. The Office of State Procurement will maintain a file of all vendor EO policies submitted in response to solicitations issued by this office. The submission is a one- time requirement, but vendors are responsible for providing updates or changes to their respective policies, and for supplying EO policies upon request to other state agencies that **must** also comply with this statute. Vendors that do not have an established EO policy will not be prohibited from receiving a contract award, but are required to submit a written statement to that effect.
3. **ALTERATION OF ORIGINAL IFB DOCUMENTS:** The original written or electronic language of the IFB documents shall not be changed or altered except by approved written addendum issued by the Office of State Procurement. This does not eliminate a Bidder from taking exception(s) to non-mandatory terms and conditions, but does clarify that the Bidder cannot change the original document's written or electronic language. If the Bidder wishes to make exception(s) to any of the original language, it **must** be submitted by the Bidder in separate written or electronic language in a manner that clearly explains the exception(s). If Bidder's/Contractor's submittal is discovered to contain alterations/changes to the original written or electronic documents, the Bidder's response may be declared as "non-responsible" and the response shall not be considered.
4. **REQUIREMENT OF AMENDMENT:** THIS IFB MAY BE MODIFIED ONLY BY AMENDMENTS WRITTEN AND AUTHORIZED BY THE OFFICE OF STATE PROCUREMENT. Bidders are cautioned to ensure that they have received or obtained, and responded to, any and all amendments to the bid prior to submission. There will be no addendums to a bid 72 hours prior to the bid opening. It is the responsibility of the vendor to check the OSP website, <http://www.arkansas.gov/dfa/procurement/bids/index.php> for any and all addendums up to that time.
5. **DELIVERY OF RESPONSE DOCUMENTS:** In accordance with the Arkansas Procurement Law and Rules, it is the responsibility of vendors to submit bids at the place, and on or before the date and time, set in the bid solicitation documents. Bid documents received at the Office of State Procurement after the date and time designated for bid opening are considered late bids and shall not be considered. Bid documents arriving late, which are to be returned and are not clearly marked, may be opened to determine for which bid the submission is intended.
6. **ADDITIONAL TERMS AND CONDITIONS:** The Office of State Procurement objects to, and shall not consider, any additional terms or conditions submitted by a bidder, including any appearing in documents attached as part of a bidder's response. In signing and submitting his bid, a bidder agrees that any additional terms or conditions, whether submitted intentionally or inadvertently, shall have no force or effect. Failure to comply with terms and conditions, including those specifying information that **must** be submitted with a bid, shall be grounds for rejecting a bid.

STATE OF ARKANSAS  
Invitation For Bid

Bid No: SP-17-0022

Page 3 of 20

7. **ANTICIPATION TO AWARD:** After complete evaluation of the solicitation, the anticipated award will be posted on the Office of State Procurement website. The purpose of the posting is to establish a specific time in which vendors and agencies are aware of the anticipated award. The bid results will be posted for a period of fourteen (14) days prior to the issuance of any award. Vendors and agencies are cautioned that these are preliminary results only and no official award will be issued prior to the end of the fourteen-day posting period. Accordingly, any reliance on these preliminary results is at the agency's/vendor's own risk.

The Office of State Procurement reserves the right to waive the Anticipation to Award when it is determined to be in the best interest of the State.

8. **PAST PERFORMANCE:** In accordance with provisions of The State Procurement Law, R7: 19-11-229 Competitive Sealed Bidding - Bid Evaluation paragraph (E) (i) & (ii): a vendor's past performance with the state may be used in the evaluation of any bid made in response to this solicitation. The past performance should not be greater than three years old and **must** be supported by written documentation on file in the Office of State Procurement at the time of the bid opening. Documentation may be in the form of a written or an electronic report, VPR (Vendor Performance Report), memo, file or any other appropriate authenticated notation of performance to the vendor files.
9. **EO-98-04 GOVERNOR'S EXECUTIVE ORDER:** Bidders should complete the Disclosure Forms issued with this bid.
10. **CURRENCY:** All bid pricing **must** be United States dollars and cents.
11. **LANGUAGE:** Bids will only be accepted in the English language.

## SECTION 1 - GENERAL INFORMATION

### 1.1 **INTRODUCTION**

This Invitation for Bid (IFB) is issued by the Office of State Procurement (OSP) for Arkansas Agriculture Department (AAD) to obtain pricing and a contract(s) for three (3) crawler tractor/dozers.

### 1.2 **ISSUING AGENCY**

**The issuing office is the sole point of contact in the State for the selection process.** Vendor questions regarding IFB related matters should be made through the State's buyer, John Leverett at 501-683-2222 or email: [john.leverett@dfa.arkansas.gov](mailto:john.leverett@dfa.arkansas.gov)

### 1.3 **CAUTION TO BIDDERS**

1. **During the time between the bid opening and contract award, any contact concerning this IFB should be initiated by the issuing office or requesting entity and not the vendor.** Specifically, the person(s) named herein will initiate all contact.

**Vendors must submit one (1) signed original IFB response on or before the date specified on page one.**

2. The State Procurement Official reserves the right to award a contract or reject a bid for any or all line items of a bid received as a result of this IFB, if it is in the best interest of the State to do so. Bids **will** be rejected for one or more reasons not limited to the following:
  - a. Failure of the vendor to submit his bid(s) on or before the deadline established by the issuing office.
  - b. Failure to sign an Official Bid Document.
  - c. Failure to complete the Official Bid Price Sheet.
  - d. Any wording by the vendor in their response to this IFB, or in subsequent correspondence, which conflicts with or takes exception to a requirement in the IFB.
  - e. Failure of any proposed goods or service to meet or exceed the specifications.

### 1.4 **BID FORMAT**

Any statement in this document that contains the word “**will**”, “**must**” or “**shall**” means that compliance with the intent of the statement is mandatory, and failure by the bidder to satisfy that intent will cause the bid to be rejected. Reference to handbooks or other technical materials as part of a response **must** not constitute the entire response and vendor **must** identify the specific page and paragraph being referenced.

### 1.5 **TYPE OF CONTRACT**

Firm

### 1.6 **PAYMENT AND INVOICE PROVISIONS**

All invoices should be forwarded to:

AAD-Forestry Commission  
Pia McDonald  
1 Natural Resources Drive  
Little Rock, AR 72205

Payment will be made in accordance with applicable State of Arkansas accounting procedures upon acceptance by Arkansas Agriculture Department (AAD). The State may not be invoiced in advance of delivery and acceptance of any vehicle. Payment will be made only after the contractor has successfully satisfied AAD as to the goods and/or services purchased. Vendors should invoice AAD by an itemized list of charges. **Purchase Order Number should be referenced on invoice.**

Selected vendor **must** be registered to receive payment and future bid notifications. If you are not a registered vendor, you may register on-line at <https://www.ark.org/vendor/index.html>

**1.7 RECORD RETENTION**

The Contractor **shall** be required to maintain all pertinent financial and accounting records and evidence pertaining to the contract in accordance with generally accepted principles of accounting and other procedures specified by the State of Arkansas. Access will be granted upon request, to State or Federal Government entities or any of their duly authorized representatives.

Financial and accounting records **shall** be made available, upon request, to the State of Arkansas' designee(s) at any time during the contract period and any extension thereof, and for five (5) years from expiration date and final payment on the contract or extension thereof.

**1.8 PROPRIETARY INFORMATION**

Proprietary information submitted in response to this (IFB) will be processed in accordance with applicable State of Arkansas procurement procedures. Bids and documents pertaining to the (IFB) become the property of the State and shall be open to public inspection subsequent to bid opening. It is the responsibility of the Vendor to identify all proprietary information. **The vendor should submit one complete copy of the response from which any proprietary information has been removed, i.e., a redacted copy.** The redacted copy should reflect the same pagination as the original, show the empty space from which information was redacted, and should be submitted on a CD or flash drive. Except for the redacted information, the redacted copy **must** be identical to the original hard copy. The vendor is responsible for ensuring the redacted copy on CD/flash drive is protected against restoration of redacted data. The redacted copy will be open to public inspection under the Freedom of Information Act (FOIA) without further notice to the vendor. If a redacted copy is not included, the entire bid will be open to public inspection with the exception of financial data (other than pricing). If the State of Arkansas deems redacted information to be subject to the FOIA the vendor will be contacted prior to sending out the information.

**1.9 RESERVATION**

This IFB does not commit the State Procurement Official to award a contract(s), to pay costs incurred in the preparation of a bid in response to this request, or to procure or contract for commodities or services.

**1.10 PRIME CONTRACTOR RESPONSIBILITY**

The selected vendor(s) **will** be required to assume prime contractor responsibility for the contract and **will** be the sole point of contact with regard to all commodities, services and support.

**1.11 CONDITIONS OF CONTRACT**

The successful bidder(s) **shall** at all times observe and comply with federal and State laws, local laws, ordinances, orders, and regulations existing at the time of or enacted subsequent to the execution of this contract which in any manner affect the completion of the work. The successful bidder(s) **shall** indemnify and save harmless the agency and all its officers, representatives, agents, and employees against any claim or liability arising from or based upon the violation of any such law, ordinance, regulation, order or decree by an employee, representative, or subcontractor of the successful bidder.

**1.12 STATEMENT OF LIABILITY**

The State will demonstrate reasonable care but **shall not** be liable in the event of loss, destruction, or theft of contractor-owned items to be delivered or to be used in the installation of deliverables. The vendor(s) is required to retain total liability until the deliverables have been accepted by the "authorized agency official." At no time will the State be responsible for or accept liability for any vendor-owned items.

**1.13 AWARD RESPONSIBILITY**

The State Procurement Official will be responsible for award and administration of any resulting contract.

**1.14 PUBLICITY**

News release(s) by a vendor pertaining to this IFB or any portion of the project shall not be made without prior written approval of the State Procurement Official. Failure to comply with this requirement is deemed to be a valid reason for disqualification of the vendor's bid. The State Procurement Official will not initiate any publicity relating to this procurement action before the contract award is completed.

**1.15 AWARD CRITERIA**

Award **shall** be made by line item to the lowest responsive, responsible bidder meeting minimum specifications.

STATE OF ARKANSAS  
Invitation For Bid

Bid No: SP-17-0022

Page 6 of 20

Bids **must** meet or exceed all defined specifications. Bids **must** meet all terms and conditions of this Invitation for Bid and the laws of the State of Arkansas.

**1.16 DELEGATION AND/OR ASSIGNMENT**

The vendor **shall not** assign the contract in whole or in part or any payment arising there from without the prior written consent of the State Procurement Official. The vendor **shall not** delegate any duties under this contract to a subcontractor unless the State Procurement Official has given written consent to the delegation.

**1.17 COST**

All charges **must** be included on the Official Bid Price Sheet and **must** include all associated cost for the goods being bid. Bid pricing **must** be valid for 90 days following IFB opening to allow sufficient time to tabulate and evaluate bid responses.

**NOTE:**

1. The State **will not** be obligated to pay any costs not identified on the Official Bid Price Sheet.
2. Any cost not identified by the bidder but subsequently incurred in order to achieve contract completion **shall** be borne by the bidder.

**1.18 DELIVERY: FOB DESTINATION: BID PRICE MUST INCLUDE ALL SHIPPING AND HANDLING COSTS.**

Deliver to:

AAD-FC Rural Fire Protection  
Attn: John Blackburn  
20 Industrial Blvd.  
Greenbrier, AR 72058

The agency requests delivery within 90 calendar days after receipt of the order. If this delivery date cannot be met, the bidder **must** state the number of days required to place the commodity in the ordering entity's designated location. Failure to state the delivery time obligates the bidder to complete delivery by the agency's requested date. Extended delivery dates may be considered when in the best interest of the state.

Delivery \_\_\_\_\_ calendar days after receipt of order.

**1.19 CANCELLATION**

In the event the State no longer needs the service or commodity specified in the contract or purchase order due to program changes, changes in laws, rules, or regulations, relocation of offices, or lack of appropriated funding, the State may cancel the contract or purchase order by giving the contractor written notice of such cancellation 30 days prior to the date of cancellation.

## SECTION 2 – CRAWLER TRACTOR/DOZER SPECIFICATIONS

### **SCOPE**

This will be a firm contract(s) for three (3) crawler tractor/dozers with bulldozer blade for Arkansas Agriculture Department. The units offered shall be the latest model in current production and shall be of good quality as to workmanship and material used.

It is required that the units be assembled, adjusted and made ready for continuous operation at time of delivery.

### **Minimum Specifications for Item 1: Crawler Tractor/Dozer with Bulldozer Blade, Plow and, 24" Track Shoe, New**

#### **OPTIONAL EQUIPMENT IS IN ADDITION TO FEDERAL AND STATE SPECIFICATIONS.**

### **UNIT OVERVIEW**

New track-type crawler tractor with bulldozer blade and ROPS/FOPS cab. Tractor **must** have proven history in fire service and working in extreme heated conditions. The tractor **must** be able to pull a fire plow and/or bulldoze fire lines without overheating. Parts and service **must** be readily available throughout the State of Arkansas.

### **SIZE**

SAE Minimum operating weight with ROPS/FOPS and blade: 18,000-20,000 pound class. John Deere 550K LGP or approved equal, with RM-1000H Fireline plow with heavy duty Fesco hitch.

### **ENGINE**

Diesel, 4 cycle, 4 or 6 cylinder, minimum 94 SAE net horsepower, (4.5 L), with turbocharger minimum. Hydraulic-operated suction fan **must** have auto reversing feature and all standard accessories. Electronically controlled governor. Fuel, oil filter system. Dry-type air cleaner with pre-cleaner and air restriction indicator. Engine lubrication pressure system with full-flow-filter. Engine coolant heater 1000 watts, 110 volt. 12 volt accessory panel where two-way radios and additional lighting can be hooked up without modification to the electrical system. Engine **must** meet emission standards in effect at time of order. Normal regeneration processes cannot inhibit the operation of tractor.

### **TRANSMISSION**

Dual-path hydrostatic transmission. Variable speeds to 6 mph. **Torque converter drive is not acceptable.** It **must** feature load-sensing, anti-stall and counter-rotation. Transmission oil reservoir **must** be steel. The tractor **must** be capable of "power turns". The transmission **must** be plumbed with remote diagnostics test ports located as to permit diagnostic procedures without removal of any significant components.

### **UNDERCARRIAGE**

Track gauge to be from 57" to 69" with 7 roller track frame and minimum of one carrier roller on each side. Track shoe shall be 24" wide, single grouser. Hydraulic track adjusters. Sealed and lubricated track chains.

### **HYDRAULIC SYSTEM**

Full flow type filters, hydraulic control valves to operate lift cylinder, tilt cylinder, and angle cylinder with auxiliary valve and lines installed for rear plow operation, quick release connections to be provided for auxiliary hydraulic hoses. Hydraulic oil reservoir **must** be steel.

### **BLADE**

Blade will be a 6-way actuated power angle, tilt, minimum 97", maximum 105" wide, with heavy-duty C-frame. Blade shall fully cover tracks. Cutting edges will be heat treated. Reversible end bits.

### **ROPS/FOPS**

Tractor shall have a roll-over and falling-object, protection structure cab, certified by the manufacturer to meet current OSHA and I.S.O. requirements.

### **PLOW**

Fesco RM-1000H Fireline plow with heavy duty Fesco Hitch, or approved equal. Minimum specs:

STATE OF ARKANSAS  
Invitation For Bid

Bid No: SP-17-0022

Page 8 of 20

DISC: 26" diameter X 3/8" thick.

COULTER BLADE: 3/8" thick X 24" diameter

COULTER ARMS: Adjustable 1" steel plate.

SPREADER BAR: 7" wide 3 1/2" flange ship and car channel.

HYDRAULIC CYLINDER: 4" bore x 12" stroke x 2" diameter ram, clevis mount, welded base. **Both ports located at the retract end with front/rear dual direction capability.**

FRAME: Side plates 9" wide, 7/8" thick high tensile steel.

PLOW SWIVEL: 2 3/16" diameter vertical pin, 1 1/2" horizontal pin, 1 1/4" diameter cylinder pin.

PLOW FRAME HITCH: 1 1/2" diameter horizontal pin, 2-position adjustable.

MOUNT BRACKET HITCH TRACTOR: 2 3/16" vertical pin, all welded construction, transport locking device, can be operated from tractor seat.

PLOW MIDDLE-BUSTER: **H500400, 20" wide manganese moly heat-treated heat-resisting steel**, fastened to middle-buster heel with two (2) 3/4" bolts.

MIDDLE-BUSTER HEEL: 1 1/4" steel plate.

SPRING ROD: 1 1/4" diameter with 1 1/4" diameter horizontal pin, adjustable.

SPRING: Compression-type, right hand wound 2 3/4" O.D. x 18" free height x 19/32" diameter alloy steel.

DISC BOXES: Ductile iron housing. Heavy duty two (2) hole both mounted on frame at 45 degree angle with 15 degree tilt. Inside sup 4.4375" O.D. Inside bearing 2.265". Outside cup 4.125" O.D. Outside bearing bore 2.250".

DEPTH SLIDE: Adjustable.

APPROACH ANGLE: 32 degree approximate.

DISC HUB: 15" diameter steel flange. 2-piece fabricated with C-1141 steel-machined spindle-pressed into flange and welded.

RECOMMENDED HORSEPOWER: 72 to 105 hp.

WEIGHT: Approximately 2000 lb.

**WINCH**

None

**ELECTRICAL**

Electronic monitor with additional gauges, engine oil pressure/engine coolant temperature. Reverse warning alarm. The tractor shall be equipped with eight work lights. One pair mounted in the grille. One pair shall be mounted overhead, facing forward, angled outboard with guards. One pair roof mounted facing forward, one pair mounted inside the rear screen facing rearward. Each pair of lights shall be switched on an independent circuit, minimum of four separate circuits, using clearly labeled switches. Each circuit shall be protected by an independent circuit breaker. Power port, 10 amps for phone and radio. Dual batteries, low maintenance.

**OPERATOR'S STATION**

A. Enclosed Cab – The operator's station shall be a fully enclosed, sound suppressed, ROPS cab. It shall be heated, air conditioned and pressurized. The Roll Over Protective Structure (ROPS) and Falling Object Protective Structure (FOPS) shall meet the requirements of the latest issues of OSHA 1910.266, SAE J1040, J231 and be fully certified.



STATE OF ARKANSAS  
Invitation For Bid

Bid No: SP-17-0022

Page 9 of 20

B. Minimum 24,000 Btu per hr. air conditioner. The condensing unit shall be mounted on the rear of the cab and equipped with maximum protection, (minimum ¼" steel guard), against damage from trees, tree limbs, brush or any other debris from entering through top of unit. AC units vented out the top are unacceptable.

C. Modular ROPS/FOPS, isolation-mounted cab, **must** conform to SAEJ1040. Cab fresh-air-intake heater/defroster and pressurizer: 18,000 Btu per hr. with air pre-cleaner and independent defroster fan **must** defog windows at any time whether the system is being used for cooling or heating. Deluxe headliner with molded air ducts for heater/defroster and air conditioner and dome light. Front windshield, doors, and rear windshield wipers & washers. Tented safety glass. 90-amp alternator minimum.

Pressurization and filter system **must** be suitable for use in forestry operations with primary use being wildfire suppression and related functions. The pressurization system shall deliver air to the operator's compartment that has been filtered through a spark arresting screen, a high efficiency particulate element (HEPA) and through an activated carbon element. The particulate media shall have an efficiency rating of 93 DOP at 0.5 micron. The media shall be fiberglass. The activated carbon element shall have an "activity rating" of 60, minimum. Any externally mounted filters shall be protected from brush damage.

D. Two (2) replacement HEPA particulate elements and two (2) replacement activated carbon elements shall be furnished upon delivery of crawler tractor.

E. Extreme-duty louvered grille.

F. Limb risers: Point-to-point, bolt-on, minimum 3" x 3" x ¼" with overhead exhaust. The right limb riser shall incorporate an inboard mounted exhaust system which routes exhaust over the canopy away from the operator. Flexible pipe sections **must** be stainless steel. Exhaust system shall be waterproof and protect engine from rainfall during idle periods.

#### **OPERATOR-PROTECTIVE FULL SCREEN PACKAGE**

A. WINDOWS: The windows shall be tempered safety glass. It shall be heat resistant to 550 degrees F. All windows shall be protected by protective screens meeting the requirements of ISO8084. The screens shall be painted black or gray. The front and side screen shall be ¼" diameter x 1 ¾" square openings made from laser cut plate. The rear screen shall be ¼" diameter x 1 ¾" square openings made from laser cut plate. Side, door, and rear screens will be hinged to facilitate window cleaning with quick release latches for securing the window screen and shall be adequately guarded and retained on the screen frame when the screen is opened. The cab windows, front, rear and doors, shall be equipped with wipers and washers.

B. OPERATOR ACCESS: The operator's compartment shall have left side and right side access doors. At a minimum, access shall be provided on the left side and an emergency escape provided on the right side. It **must** be accessible from the outside to permit rescue of an unconscious operator. Operator compartment access **must** meet the requirements of ISO8084. The entrance door(s) and windows **must** be capable of being secured in the open position to allow for natural cross flow ventilation. Doors **must** retain full opening and latching capability.

C. ACCESSORIES: Tractors will be equipped with: Crank case guard with closed-eye front tow hook. Full bottom guard front and rear ½" minimum thickness with removable cleanout sections. Engine enclosure which includes quick release perforated side panels. All manufacturer's hydraulic hose shields. Lift cylinder shields. Air intake guard if air intake above hood. Master electrical disconnect switch. Electric hour meter. Seat belt. Vandalism protective guards for instrument panel and cap locks for fuel, water, battery and hydraulic system. Two tractor tie down rings on each roller frame.

#### **GENERAL TERMS AND CONDITIONS**

The units offered shall be the latest improved model in current production and shall be of good quality as to workmanship and material used.

It is required that the units be assembled, adjusted and made ready for continuous operation at time of delivery.

#### **MANUALS**

The successful bidder **must** supply two (2) sets of service, parts, technical and operating manuals for each item awarded.

**WARRANTY/SERVICE**

Warranty shall cover all labor, parts and transportation cost to the location of the equipment for twelve (12) months.

**Warranty shall begin when unit is placed in service.** There shall be an authorized dealer staffed with qualified serviceman and with provisions for storing a representative supply of parts for equipment offered and with provisions for securing parts from the manufacturer within forty-eight (48) hours.

**POWERTRAIN WARRANTY**

A manufacturer's five (5) year, 5000 hour, extended powertrain warranty shall be included.

**TRAINING**

The successful bidder **must** furnish four (4) hours of training for tractor/dozer operator. Training shall include operational, service and safety training.

**Manufacturer's cut sheet(s), with specifications of unit being bid, should be included with bid response.**

**Minimum Specifications for Item 2: Crawler Tractor/Dozer with Bulldozer Blade, Plow and, 18" Track Shoe, New**

**OPTIONAL EQUIPMENT IS IN ADDITION TO FEDERAL AND STATE SPECIFICATIONS.**

**UNIT OVERVIEW**

New, track-type crawler tractor/dozer with blade and ROPS and FOPS type cab. Tractor/dozer **must** have proven history in fire service and working in extreme heated conditions. The tractor **must** be able to pull a fire plow and bulldoze fire lines without overheating or otherwise malfunctioning. Parts and service **must** be readily available throughout the state of Arkansas. Primary consideration is for reliability and operator safety.

The units offered shall be the latest improved model in current production and shall be of good quality as to workmanship and material used.

**SIZE**

SAE minimum operating weight with cab, ROPS and blade: 18,000-20,000 pound class. John Deere 550K XLT with RM-1000H Fireline plow with heavy duty Fesco hitch or approved equal.

**ENGINE**

Diesel, 4-cycle, 4 or 6 cylinder, 94 SAE net horsepower, (4.5 L), turbocharged with charge air cooler, minimum. Hydraulic-operated suction fan with auto reversing feature and all standard accessories. Electronically controlled governor. Fuel, oil filter system. Dry-type air cleaner with pre-cleaner and air restriction indicator. Engine lubrication pressure system with full-flow filter. Engine coolant heater 1000 watt 110 volt block heater. 12 volt accessory panel shall provide access for two-way radios and additional lighting to be connected to power and used without modification to the electrical system. Normal regeneration process shall not inhibit operation of tractor.

Engine **must** meet emission standards in effect at time of order.

**TRANSMISSION**

Dual-path hydrostatic transmission. Variable speeds to 6 mph. **Torque converter drive is not acceptable.** Transmission **must** feature: load-sensing, anti-stall and counter-rotation. Tractor/dozer **must** be capable of "power turns". The transmission **must** be plumbed with remote diagnostics test ports located as to permit diagnostic procedures without removal of any significant components.

**UNDERCARRIAGE**

Track gauge will be from 57" to 69", with 7-roller track frame and minimum of one carrier roller on each side. Track shoe shall be 18" wide single grouser with hydraulic track adjusters. Sealed and lubricated track chains. Full-length track roller guards. Heavy duty sealed and lubricated undercarriage.

**HYDRAULIC SYSTEM**

Full flow-type filters. Hydraulic control valves to operate lift cylinder. Tilt cylinder and angle cylinder with auxiliary valve and lines installed for rear plow operation. Quick release connections shall be provided for auxiliary hydraulic hoses. Hydraulic oil reservoir **must** be steel.

**BLADE**

Blade will be a 6-way actuated power angle tilt, minimum 97", maximum 102" wide, with heavy-duty C-frame. Blade **must** fully cover tracks. Cutting edges will be heat-treated. Reversible end bits.

**ROPS**

Tractor will have a roll-over protection structure cab certified by the manufacturer to meet current OSHA and I.S.O. requirements.

**PLOW**

RM-1000H Fireline Plow with heavy duty Fesco Hitch or approved equal. Minimum specs:

DISC: 26" diameter X 3/8" thick.

COULTER BLADE: 3/8" thick X 24" diameter

STATE OF ARKANSAS  
Invitation For Bid

Bid No: SP-17-0022

Page 12 of 20

COULTER ARMS: Adjustable 1" steel plate.

SPREADER BAR: 7" wide 3 1/2" flange ship and car channel.

HYDRAULIC CYLINDER: 4" bore x 12" stroke x 2" diameter ram, clevis mount, welded base. **Both ports located at the retract end with front/rear dual direction capability.**

FRAME: Side plates 9" wide, 7/8" thick high tensile steel.

PLOW SWIVEL: 2 3/16" diameter vertical pin, 1 1/2" horizontal pin, 1 1/4" diameter cylinder pin.

PLOW FRAME HITCH: 1 1/2" diameter horizontal pin, 2-position adjustable.

MOUNT BRACKET HITCH TRACTOR: 2 3/16" vertical pin, all welded construction, transport locking device, can be operated from tractor seat.

PLOW MIDDLE-BUSTER: H500400, 20" wide Manganese-Moly heat-treated heat-resisting steel, fastened to middle-buster heel with two (2) 3/4" bolts.

MIDDLE-BUSTER HEEL: 1 1/4" steel plate.

SPRING ROD: 1 1/4" diameter with 1 1/4" diameter horizontal pin, adjustable.

SPRING: Compression-type, right hand wound 2 3/4" O.D. x 18" free height x 19/32" diameter alloy steel.

DISC BOXES: Ductile iron housing. Heavy duty two (2) hole both mounted on frame at 45 degree angle with 15 degree tilt. Inside sup 4.4375" O.D. Inside bearing 2.265". Outside cup 4.125" O.D. Outside bearing bore 2.250".

DEPTH SLIDE: Adjustable.

APPROACH ANGLE: Approximately 32 degrees.

DISC HUB: 15" diameter steel flange. 2-piece fabricated with C-1141 steel-machined spindle-pressed into flange and welded.

RECOMMENDED HORSEPOWER: 72 to 105 hp.

APPROXIMATE WEIGHT: 2000 lb.

**WINCH**

None

**ELECTRICAL**

Electronic monitor with additional gauges for engine oil pressure and engine coolant temperature. Reverse warning alarm. The tractor shall be equipped with eight work lights. One pair mounted in the grille. One pair shall be mounted overhead, facing forward, angled outboard with guards. One pair roof-mounted facing forward. One pair mounted inside the rear screen facing rearward. Each pair of lights shall be switched on an independent circuit, minimum of four separate circuits, using clearly labeled switches. Each circuit shall be protected by an independent circuit breaker. Dual batteries, low maintenance. Power port, 10 amps with connections for phone and radio.

**OPERATOR'S STATION**

A. Enclosed Cab - The operator's station shall be a fully enclosed, sound suppressed, ROPS cab. It shall be heated, air conditioned and pressurized. The Roll-Over Protective Structure (ROPS) and Falling Object Protective Structure (FOPS) shall meet the requirements of the latest issues of OSHA 1910.266, SAE J1040, J231 and be fully certified.

B. Minimum 24,000 Btu per hour air conditioner – The condensing unit shall be mounted on the rear of the cab and equipped with maximum protection, (minimum 1/4" steel guard), against damage from trees, tree limbs, brush or any other

debris from entering through top of unit. AC units vented out the top **must** have protection to prevent debris from entering unit.

C. Modular ROPS/FOPS, isolation-mounted cab, **must** conform to SAEJ1040. Cab fresh-air-intake heater/defroster and pressurizer: minimum 18,000 Btu per hr. with air pre-cleaner and independent defroster fan **must** defog windows at any time whether the system is being used for cooling or heating. Deluxe headliner with molded air ducts for heater/defroster and air conditioner and dome light. Front windshield, doors, and rear windshield wipers & washers. Tented safety glass. 90-amp alternator minimum.

Pressurization and filter system **must** be suitable for use in forestry operations with primary use being wildfire suppression and related functions. The pressurization system shall deliver air to the operator's compartment that has been filtered through a spark arresting screen, a high efficiency particulate element (HEPA) and through an activated carbon element. The particulate media shall have a minimum efficiency rating of 93 DOP at 0.5 micron. The media shall be fiberglass. The activated carbon element shall have an "activity rating" of 60, minimum. Any externally mounted filters shall be protected from brush damage.

D. Two (2) replacement HEPA particulate elements and two (2) replacement activated, carbon elements shall be furnished upon delivery of crawler tractor.

E. Extreme-duty louvered grille

F. Limb risers: point-to-point (bolt-on) (min. 3" x 3" x 1/4") with overhead exhaust.

The right limb riser should incorporate an inboard mounted exhaust which routes exhaust over the canopy away from the operator. Flexible pipe sections **must** be stainless steel. Exhaust system shall be waterproof and protect the engine from rainfall during idle periods.

#### **OPERATOR-PROTECTIVE FULL SCREEN PACKAGE**

A. WINDOWS: The windows shall be tempered safety glass, heat resistant to 550 degrees Fahrenheit. All windows shall be protected by protective screens meeting the requirements of ISO 8084. The screens shall be painted black or gray. The front and side screen shall be 1/4" x 1 3/4" square openings made from laser-cut-plate. The rear screen shall be 1/4" x 1" square openings made from laser-cut-plate. Side, door, and rear screens are to be hinged to facilitate window cleaning with quick release latches for securing the window screens and shall be adequately guarded and retained on the screen frame when the screen is opened. The cab windows front and rear, and doors shall be equipped with wipers and washers.

B. OPERATOR ACCESS: The operator's compartment shall have left side and right side access doors. At a minimum, access shall be provided on the left side and an emergency escape provided on the right side. It **must** be accessible from the outside to permit rescue of an unconscious operator. Operator compartment access **must** meet the requirements of ISO 8084. The entrance doors and windows **must** be capable of being secured in the open position to allow for natural cross-flow ventilation. Doors **must** retain full opening and latching capability.

C. COVER, GUARDS & SHIELDS: Tractor/dozer will be equipped with crank case guard with closed eye front tow hook full bottom guard front and rear, 1/2" minimum thickness with removable cleanout sections. Engine enclosure which includes quick release perforated side panels, all manufacturers hydraulic hose shields, lift cylinder shields, air intake guard if air intake above the hood, master electrical disconnect switch, electric hour meter, seat belt, vandalism protective guards for instrument panel and cap-locks for fuel, water, battery and hydraulic system hose protection. Two tractor tie-down rings on each roller frame.

#### **GENERAL TERMS AND CONDITIONS**

The units offered shall be the latest improved model in current production and shall be of good quality as to workmanship and material used.

It is required that the units be assembled, adjusted and made ready for continuous operation at time of delivery.

#### **MANUALS**

The successful bidder **must** supply a set of service, parts and operating manuals and one Tech manual for each model awarded. One extra set for RFP shop.

**WARRANTY/SERVICE**

There shall be an authorized dealer staffed with qualified serviceman and with provisions for storing a representative supply of parts for equipment offered and with provisions for securing parts from the manufacturer within forty-eight (48) hours.

Warranty shall cover all labor, parts and transportation cost to the location of the equipment for twelve (12) months.

**Warranty will begin when unit is placed in service.**

It is required that the units be assembled, adjusted and made ready for continuous operation at time of delivery.

**POWERTRAIN WARRANTY**

A manufacturer's 5 year, 5000 hour, extended powertrain warranty shall be included.

**TRAINING**

The successful bidder **must** furnish four (4) hours of training for tractor/dozer operator. Training shall include operational, service and safety training.

**Manufacturer's cut sheet(s), with specifications of unit being bid, should be included with bid response.**

**Minimum Specifications for Item 3: Crawler Tractor/Dozer with Bulldozer Blade, Winch, and 18" Track Shoe, New**

**OPTIONAL EQUIPMENT IS IN ADDITION TO FEDERAL AND STATE SPECIFICATIONS.**

**UNIT OVERVIEW**

New, track-type crawler tractor/dozer with blade, ROPS and FOPS type cab. Tractor/dozer **must** have proven history in fire service and working in extreme heated conditions. The tractor **must** be able to pull a fire plow and bulldoze fire lines without overheating or otherwise malfunctioning. Parts and service **must** be readily available throughout the state of Arkansas. Primary consideration is for reliability and operator safety.

**SIZE**

SAE minimum operating weight with cab, ROPS and blade: 18,000-20,000 pound class. John Deere 550K XLT with winch or approved equal.

**ENGINE**

Diesel, 4-cycle, 4 or 6 cylinder, minimum 94 SAE net horsepower, (4.5 L), turbocharged with charge air cooler. Hydraulic-operated suction fan **must** have auto reversing feature and all standard accessories. Electronically controlled governor. Fuel, oil filter system. Dry-type air cleaner with pre-cleaner and air restriction indicator. Engine lubrication pressure system with full-flow filter. Engine coolant heater: 1000 watt, 110 volt block heater. 12 volt accessory panel allowing two-way radios and additional lighting to be connected to power and used without modification to the electrical system. Normal regeneration process shall not inhibit operation of tractor. Engine **must** meet emission standards in effect at time of order.

**TRANSMISSION**

Dual-path hydrostatic transmission. Variable speeds to 6 mph. **Torque converter drive is not acceptable.** Transmission **must** feature: load-sensing, anti-stall and counter-rotation. Transmission oil reservoir **must** be steel. Tractor/dozer **must** be capable of "power turns". The transmission **must** be plumbed with remote diagnostics test ports located as to permit diagnostic procedures without removal of any significant components.

**UNDERCARRIAGE**

Track gauge will be from 57" to 69", with 7-roller track frame and minimum of one carrier roller on each side. Track shoe shall be 18" wide single grouser with hydraulic track adjusters. Full-length track roller guards. Heavy duty sealed and lubricated undercarriage.

**HYDRAULIC SYSTEM**

Full flow-type filters. Hydraulic control valves to operate lift cylinder. Tilt cylinder and angle cylinder with auxiliary valve and lines installed for rear plow operation. Quick release connections shall be provided for auxiliary hydraulic hoses. Hydraulic oil reservoir **must** be steel.

**BLADE**

Blade will be a 6-way actuated power angle tilt, minimum 97", maximum 102" wide, with heavy-duty C-frame. Blade **must** fully cover tracks. Cutting edges will be heat-treated. Reversible end bits.

**ROPS**

Tractor will have a roll-over protection structure cab certified by the manufacturer to meet current OSHA and I.S.O. requirements.

**PLOW**

None

**WINCH**

The tractor shall be equipped with a rear mount, mechanically driven, or hydraulically driven winch. The winch shall be capable of a minimum of 35,000 pound bare drum line pull. The winch shall be equipped with "low speed" gearing intended for "retrieval" applications. The winch shall feature "power in," "power out," "brake on," "brake off," and free spool positions. The winch shall be equipped with a four-roller fairlead. The winch shall be equipped with ¾" x 125' wire rope, Independent Wire Rope Core (IWRC), 6x19 construction, with pull hook swaged to wire rope.

### **ELECTRICAL**

Electronic monitor with additional gauges for engine oil pressure and engine coolant temperature. Reverse warning alarm. The tractor shall be equipped with eight work lights. One pair mounted in the grille. One pair shall be mounted overhead, facing forward, angled outboard with guards. One pair roof-mounted facing forward. One pair mounted inside the rear screen facing rearward. Each pair of lights shall be switched on an independent circuit, minimum of four separate circuits, using clearly labeled switches. Each circuit shall be protected by an independent circuit breaker. Power port, 10 amps for phone and radio. Dual batteries, low maintenance.

### **OPERATOR'S STATION**

A. The operator's station shall be a fully enclosed, sound suppressed, ROPS cab. It shall be heated, air conditioned and pressurized. The Roll-Over Protective Structure (ROPS) and Falling Object Protective Structure (FOPS) shall meet the requirements of the latest issues of OSHA 1910.266, SAE J1040, J231 and be fully certified.

B. Minimum 24,000 Btu per hour air conditioner – The condensing unit shall be mounted on the rear of the cab and equipped with maximum protection (minimum 1/4" steel guard) against damage from trees, tree limbs, brush or any other debris from entering through top of unit. AC units vented out the top **must** have protection to prevent debris from entering unit.

C. Modular ROPS/FOPS, isolation-mounted cab, **must** conform to SAEJ1040. Cab fresh-air-intake heater/defroster and pressurizer: 18,000 Btu per hr. with air pre-cleaner and independent defroster fan **must** defog windows at any time whether the system is being used for cooling or heating. Deluxe headliner with molded air ducts for heater/defroster and air conditioner and dome light. Front windshield, doors, and rear windshield wipers & washers. Tinted safety glass. 90-amp alternator minimum.

Pressurization and filter system **must** be suitable for use in forestry operations with primary use being wildfire suppression and related functions. The pressurization system shall deliver air to the operator's compartment that has been filtered through a spark arresting screen, a high efficiency particulate element (HEPA) and through an activated carbon element. The particulate media shall have a minimum efficiency rating of 93 DOP at 0.5 micron. The media shall be fiberglass. The activated carbon element shall have an "activity rating" of 60, minimum. Any externally mounted filters shall be protected from brush damage.

D. Two (2) replacement HEPA particulate elements and two (2) replacement activated carbon elements shall be furnished upon delivery of crawler tractor.

E. Extreme-duty louvered grille

F. Limb risers: Point-to-point, bolt-on, minimum 3" x 3" x 1/4" with overhead exhaust. The right limb riser shall incorporate an inboard mounted exhaust system which routes exhaust over the canopy away from the operator. Flexible pipe sections **must** be stainless steel. Exhaust system shall be waterproof and protect engine from rainfall during idle periods.

### **OPERATOR-PROTECTIVE FULL SCREEN PACKAGE**

A. WINDOWS: The windows shall be tempered safety glass, heat resistant to 550 degrees Fahrenheit. All windows shall be protected by protective screens meeting the requirements of ISO 8084. The screens shall be painted black or gray. The front and side screen shall be 1/4" x 1 3/4" square openings made from laser-cut-plate. The rear screen shall be 1/4" x 1" square openings made from laser-cut-plate. Side, door, and rear screens are to be hinged to facilitate window cleaning with quick release latches for securing the window screens and shall be adequately guarded and retained on the screen frame when the screen is opened. The cab windows, front and rear, and doors shall be equipped with wipers and washers.

B. OPERATOR ACCESS: The operator's compartment shall have left side and right side access doors. At a minimum, access shall be provided on the left side and an emergency escape provided on the right side. It **must** be accessible from the outside to permit rescue of an unconscious operator. Operator compartment access **must** meet the requirements of ISO 8084. The entrance doors and windows **must** be capable of being secured in the open position to allow for natural cross-flow ventilation. Doors **must** retain full opening and latching capability.

C. COVER, GUARDS & SHIELDS: Tractor/dozer will be equipped with crank case guard with closed eye front tow hook, full bottom guard front and rear, 1/2" minimum thickness with removable cleanout sections. Engine enclosure which includes quick release perforated side panels, all manufacturers hydraulic hose shields, lift cylinder shields, air intake guard if air



intake above the hood, master electrical disconnect switch, electric hour meter, seat belt, vandalism protective guards for instrument panel and cap-locks for fuel, water, battery and hydraulic system hose protection. Two tractor tie-down rings on each roller frame.

**GENERAL TERMS AND CONDITIONS**

The units offered shall be the latest improved model in current production and shall be of good quality as to workmanship and material used.

It is required that the units be assembled, adjusted and made ready for continuous operation at time of delivery.

**MANUALS**

The successful bidder **must** supply two (2) sets of service, parts, technical and operating manuals for each item awarded.

**WARRANTY/SERVICE**

Warranty shall cover all labor, parts and transportation cost to the location of the equipment for twelve (12) months.

**Warranty shall begin when unit is placed in service.** There shall be an authorized dealer staffed with qualified serviceman and with provisions for storing a representative supply of parts for equipment offered and with provisions for securing parts from the manufacturer within forty-eight (48) hours.

**POWERTRAIN WARRANTY**

A manufacturer's five (5) year, 5000 hour, extended powertrain warranty shall be included.

**TRAINING**

The successful bidder **must** furnish four (4) hours of training for tractor/dozer operator. Training shall include operational, service and safety training.

**Manufacturer's cut sheet(s), with specifications of unit being bid, should be included with bid response.**

STATE OF ARKANSAS  
Invitation For Bid

Bid No: SP-17-0022

Page 18 of 20

**OFFICIAL BID PRICE SHEET**

ITEM	QTY	DESCRIPTION	Unit Price	Total Price
1	1	Crawler Tractor/Dozer, with Plow, 24" Track Shoe, New	\$_____	\$_____

Make & model bid: \_\_\_\_\_

ITEM	QTY	DESCRIPTION	Unit Price	Total Price
2	1	Crawler Tractor/Dozer, with Plow, 18" Track Shoe, New	\$_____	\$_____

Make & model bid: \_\_\_\_\_

ITEM	QTY	DESCRIPTION	Unit Price	Total Price
3	1	Crawler Tractor/Dozer, with Winch, 18" Track Shoe, New	\$_____	\$_____

Make & model bid: \_\_\_\_\_

STATE OF ARKANSAS  
Invitation For Bid

Bid No: SP-17-0022

Page 19 of 20

**STANDARD TERMS AND CONDITIONS**

**1. GENERAL**

Any special terms and conditions included in the invitation for bid override these standard terms and conditions. The standard terms and conditions and any special terms and conditions become part of any contract entered into if any or all parts of the bid are accepted by the State of Arkansas.

**2. ACCEPTANCE AND REJECTION**

The state reserves the right to accept or reject all or any part of a bid or any and all bids, to waive minor technicalities, and to award the bid to best serve the interest of the state.

**3. BID SUBMISSION**

Bids must be submitted to the Office of State Procurement on this form, with attachments when appropriate, on or before the date and time specified for bid opening. If this form is not used, the bid may be rejected. The bid must be typed or printed in ink. The signature must be in ink. Unsigned bids will be disqualified. The person signing the bid should show title or authority to bind his firm in a contract. Each bid should be placed in a separate envelope completely and properly identified. Late bids will not be considered under any circumstances.

**4. PRICES**

Bid unit price F.O.B. destination. In case of errors in extension, unit prices shall govern. Prices are firm and not subject to escalation unless otherwise specified in the bid invitation. Unless otherwise specified, the bid must be firm for acceptance for thirty days from the bid opening date. "Discount from list" bids are not acceptable unless requested in the bid invitation.

**5. QUANTITIES**

Quantities stated in **term contracts** are estimates only, and are not guaranteed. Bid unit price on the estimated quantity and unit of measure specified. The state may order more or less than the estimated quantity on term contracts. Quantities stated on **firm contracts** are actual requirements of the ordering agency.

**6. BRAND NAME REFERENCES**

Any catalog brand name or manufacturer's reference used in the bid invitation is descriptive only, not restrictive, and used to indicate the type and quality desired. Bids on brands of like nature and quality will be considered. If bidding on other than referenced specifications, the bid must show the manufacturer, brand or trade name, and other descriptions, and should include the manufacturer's illustrations and complete descriptions of the product offered. The state reserves the right to determine whether a substitute offered is equivalent to and meets the standards of the item specified, and the state may require the bidder to supply additional descriptive material. The bidder guarantees that the product offered will meet or exceed specifications identified in this bid invitation. If the bidder takes no exception to specifications or reference data in this bid he will be required to furnish the product according to brand names, numbers, etc., as specified in the invitation.

**7. GUARANTY**

All items bid shall be newly manufactured, in first-class condition, latest model and design, including, where applicable, containers suitable for shipment and storage, unless otherwise indicated in the bid invitation. The bidder hereby guarantees that everything furnished hereunder will be free from defects in design, workmanship and material, that if sold by drawing, sample or specification, it will conform thereto and will serve the function for which it was furnished. The bidder further guarantees that if the items furnished hereunder are to be installed by the bidder, such items will function properly when installed. The bidder also guarantees that all applicable laws have been complied with relating to construction, packaging, labeling and registration. The bidder's obligations under this paragraph shall survive for a period of one year from the date of delivery, unless otherwise specified herein.

**8. SAMPLES**

Samples or demonstrators, when requested, must be furnished free of expense to the state. Each sample should be marked with the bidder's name and address, bid number and item number. If samples are not destroyed during reasonable examination they will be returned at bidder's expense, if requested, within ten days following the opening of bids. All demonstrators will be returned after reasonable examination.

**9. TESTING PROCEDURES FOR SPECIFICATIONS COMPLIANCE**

Tests may be performed on samples or demonstrators submitted with the bid or on samples taken from the regular shipment. In the event products tested fail to meet or exceed all conditions and requirements of the specifications, the cost of the sample used and the reasonable cost of the testing shall be borne by the bidder.

**10. AMENDMENTS**

The bid cannot be altered or amended after the bid opening except as permitted by regulation.

**11. TAXES AND TRADE DISCOUNTS**

Do not include state or local sales taxes in the bid price. Trade discounts should be deducted from the unit price and the net price should be shown in the bid.

**12. AWARD**

**Term Contract:** A contract award will be issued to the successful bidder. It results in a binding obligation without further action by either party. This award does not authorize shipment. Shipment is authorized by the receipt of a purchase order from the ordering agency.

**Firm Contract:** A written state purchase order authorizing shipment will be furnished to the successful bidder.

**13. LENGTH OF CONTRACT**

The invitation for bid will show the period of time the term contract will be in effect.

**14. DELIVERY ON FIRM CONTRACTS**

The invitation for bid will show the number of days to place a commodity in the ordering agency's designated location under normal conditions. If the bidder cannot meet the stated delivery, alternate delivery schedules may become a factor in an award. The Office of State Procurement has the right to extend delivery if reasons appear valid. If the date is not acceptable, the agency may buy elsewhere and any additional cost will be borne by the vendor.

STATE OF ARKANSAS  
Invitation For Bid

Bid No: SP-17-0022

Page 20 of 20

**15. DELIVERY REQUIREMENTS**

No substitutions or cancellations are permitted without written approval of the Office of State Procurement. Delivery shall be made during agency work hours only 8:00 a.m. to 4:30 p.m., unless prior approval for other delivery has been obtained from the agency. Packing memoranda shall be enclosed with each shipment.

**16. STORAGE**

The ordering agency is responsible for storage if the contractor delivers within the time required and the agency cannot accept delivery.

**17. DEFAULT**

All commodities furnished will be subject to inspection and acceptance of the ordering agency after delivery. Back orders, default in promised delivery, or failure to meet specifications authorize the Office of State Procurement to cancel this contract or any portion of it and reasonably purchase commodities elsewhere and charge full increase, if any, in cost and handling to the defaulting contractor. The contractor must give written notice to the Office of State Procurement and ordering agency of the reason and the expected delivery date. Consistent failure to meet delivery without a valid reason may cause removal from the bidders list or suspension of eligibility for award.

**18. VARIATION IN QUANTITY**

The state assumes no liability for commodities produced, processed or shipped in excess of the amount specified on the agency's purchase order.

**19. INVOICING**

The contractor shall be paid upon the completion of all of the following: (1) submission of an original and the specified number of copies of a properly itemized invoice showing the bid and purchase order numbers, where itemized in the invitation for bid, (2) delivery and acceptance of the commodities and (3) proper and legal processing of the invoice by all necessary state agencies. Invoices must be sent to the "Invoice To" point shown on the purchase order.

**20. STATE PROPERTY**

Any specifications, drawings, technical information, dies, cuts, negatives, positives, data or any other commodity furnished to the contractor hereunder or in contemplation hereof or developed by the contractor for use hereunder shall remain property of the state, be kept confidential, be used only as expressly authorized and returned at the contractor's expense to the F.O.B. point properly identifying what is being returned.

**21. PATENTS OR COPYRIGHTS**

The contractor agrees to indemnify and hold the State harmless from all claims, damages and costs including attorneys' fees, arising from infringement of patents or copyrights.

**22. ASSIGNMENT**

Any contract entered into pursuant to this invitation for bid is not assignable nor the duties thereunder delegable by either party without the written consent of the other party of the contract.

**23. OTHER REMEDIES**

In addition to the remedies outlined herein, the contractor and the state have the right to pursue any other remedy permitted by law or in equity.

**24. LACK OF FUNDS**

The state may cancel this contract to the extent funds are no longer legally available for expenditures under this contract. Any delivered but unpaid for goods will be returned in normal condition to the contractor by the state. If the state is unable to return the commodities in normal condition and there are no funds legally available to pay for the goods, the contractor may file a claim with the Arkansas Claims Commission. If the contractor has provided services and there are no longer funds legally available to pay for the services, the contractor may file a claim.

**25. DISCRIMINATION**

In order to comply with the provision of Act 954 of 1977, relating to unfair employment practices, the bidder agrees that: (a) the bidder will not discriminate against any employee or applicant for employment because of race, sex, color, age, religion, handicap, or national origin; (b) in all solicitations or advertisements for employees, the bidder will state that all qualified applicants will receive consideration without regard to race, color, sex, age, religion, handicap, or national origin; (c) the bidder will furnish such relevant information and reports as requested by the Human Resources Commission for the purpose of determining compliance with the statute; (d) failure of the bidder to comply with the statute, the rules and regulations promulgated thereunder and this nondiscrimination clause shall be deemed a breach of contract and it may be cancelled, terminated or suspended in whole or in part; (e) the bidder will include the provisions of items (a) through (d) in every subcontract so that such provisions will be binding upon such subcontractor or vendor.

**26. CONTINGENT FEE**

The bidder guarantees that he has not retained a person to solicit or secure this contract upon an agreement or understanding for a commission, percentage, brokerage or contingent fee, except for retention of bona fide employees or bona fide established commercial selling agencies maintained by the bidder for the purpose of securing business.

**27. ANTITRUST ASSIGNMENT**

As part of the consideration for entering into any contract pursuant to this invitation for bid, the bidder named on the front of this invitation for bid, acting herein by the authorized individual or its duly authorized agent, hereby assigns, sells and transfers to the State of Arkansas all rights, title and interest in and to all causes of action it may have under the antitrust laws of the United States or this state for price fixing, which causes of action have accrued prior to the date of this assignment and which relate solely to the particular goods or services purchased or produced by this State pursuant to this contract.

**28. DISCLOSURE**

Failure to make any disclosure required by Governor's Executive Order 98-04, or any violation of any rule, regulation, or policy adopted pursuant to that order, shall be a material breach of the terms of this contract. Any contractor, whether an individual or entity, who fails to make the required disclosure or who violates any rule, regulation, or policy shall be subject to all legal remedies available to the agency.