

ADPHT-26-014 MINIMUM SPECIFICATIONS ATTACHMENT 1

Polaris Ranger XP 1000 Premium UTV Minimum Specifications (or equivalent see Section 3.3 C.)

Engine & Drivetrain

- Cooling: Liquid
- Cylinders Minimum Displacement: 999cc
- Drive System Type: High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode
- Engine Type: ProStar 4-Stroke Twin Cylinder DOHC
- Fuel System/Battery: Electronic Fuel Injection
- Minimum Horsepower: 82 HP
- Transmission/Final Drive: Gen 2 Automatic PVT H/L/N/R/P; Shaft

Dimensions

- Bed Box Dimensions (L x W x H) 36.75 x 54.25 x 12.5 in (93 x 138 x 32 cm)
- Box Capacity: 1000 lbs. (454 kg) California Models: 600 lbs. (272 kg)
- Estimated Dry Weight: 1,684 lbs. (764 kg)
- Minimum Fuel Capacity: 11.5 gal (43.5 L)
- Minimum Ground Clearance: 14 in (36 cm)
- GVW: 3,600 lb. (1,633 kg)
- Hitch Towing Rating: 2,500 lb. (1,134 kg)
- Hitch Type: Standard 2 in (5 cm) Receiver
- Overall Vehicle Size (L x W x H) 120 x 62.5 x 79.5 in. (305 x 158 x 201 cm)
- Minimum Payload Capacity: 1,500 lb. (680 kg); California Models: 1,100 lb. (499 kg)
- Minimum Person Capacity: 3
- Water Fording Height: Equal to the Floorboards
- Minimum Wheelbase: 81 in (206 cm)

Brakes

- Front/Rear Brakes: 4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
- Parking Brake: Park in-transmission

Additional Specifications

- Adjustable Driver Seat: Standard
- Cargo System: Lock & Ride®
- Preferred Color / Graphics: Orange
- Electronic Power Steering: High Output EPS
- Instrumentation: Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt

Reminder, DC Outlet, USB Charge Port, Automatic Speed Limiting in 2 mph increments starting at 16 mph to max speed.

- Lighting: Dual LED Headlights, 1250lm Low Beam, 2300lm High Beam, Dual LED Taillights
- Other Standard Features: Front Bumper with Integrated Winch, Plow & LED Mounts, Premium Cut & Sew Seats with Contoured Seatbacks and Embroidered Polaris Branding, Polaris HD 4500 lb. Synthetic Rope Winch with Autostop and Wireless Remote, Factory-Installed Poly Sport Roof, Single Latch Cab Nets, Polaris Pulse Electrical System (6 position), 12V Accessory Outlet, Battery Trickle-Charging Outlet, USB Outlet
- RIDE COMMAND+ Available as Accessory
- Tilt Steering: Standard

Tires / Wheels

- Front Tires: 29 x 9-14; PRO ARMOR X-TERRAIN
- Rear Tires: 29 x 11-14; PRO ARMOR X-TERRAIN
- Tire Ply Rating: 8-Ply Rated
- Wheels: Aluminum

Suspension

- Front: Suspension Dual A-Arm, 10 in (25.4 cm)
- Rear: Suspension Dual A-Arm IRS, 10 in (25.4 cm)
- Minimum Turning Radius: 13 ft. (4.0 m)

Doors

- Manual Crank Window Doors, Front, Poly, Set of 2

Delivery Address

Devil's Den State Park
11333 West AR Hwy 74
West Fork, AR 72774

BRAND and MODEL BID: _____

BID PRICING: Including all delivery fees (DO NOT INCLUDE SALES TAX) (LIST PRICING EVEN IF ATTACHING QUOTE)

\$ _____ Each (Quantity of 1)

ADPHT-26-00x MINIMUM SPECIFICATIONS ATTACHMENT 2

Polaris Ranger XP 1000 Premium UTV Minimum Specifications (or equivalent see Section 3.3 C.)

Engine & Drivetrain

- Cooling: Liquid
- Cylinders Minimum Displacement: 999cc
- Drive System Type: High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode
- Engine Type: ProStar 4-Stroke Twin Cylinder DOHC
- Fuel System/Battery: Electronic Fuel Injection
- Minimum Horsepower: 82 HP
- Transmission/Final Drive: Gen 2 Automatic PVT H/L/N/R/P; Shaft

Dimensions

- Bed Box Dimensions (L x W x H) 36.75 x 54.25 x 12.5 in (93 x 138 x 32 cm)
- Box Capacity: 1000 lbs. (454 kg) California Models: 600 lbs. (272 kg)
- Estimated Dry Weight: 1,684 lbs. (764 kg)
- Minimum Fuel Capacity: 11.5 gal (43.5 L)
- Minimum Ground Clearance: 14 in (36 cm)
- GVW: 3,600 lb. (1,633 kg)
- Hitch Towing Rating: 2,500 lb. (1,134 kg)
- Hitch Type: Standard 2 in (5 cm) Receiver
- Overall Vehicle Size (L x W x H) 120 x 62.5 x 79.5 in. (305 x 158 x 201 cm)
- Minimum Payload Capacity: 1,500 lb. (680 kg); California Models: 1,100 lb. (499 kg)
- Minimum Person Capacity: 3
- Water Fording Height: Equal to the Floorboards
- Minimum Wheelbase: 81 in (206 cm)

Brakes

- Front/Rear Brakes: 4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
- Parking Brake: Park in-transmission

Additional Specifications

- Adjustable Driver Seat: Standard
- Cargo System: Lock & Ride®
- Preferred Color / Graphics: Orange
- Electronic Power Steering: High Output EPS
- Instrumentation: Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt

Reminder, DC Outlet, USB Charge Port, Automatic Speed Limiting in 2 mph increments starting at 16 mph to max speed.

- Lighting: Dual LED Headlights, 1250lm Low Beam, 2300lm High Beam, Dual LED Taillights
- Other Standard Features: Front Bumper with Integrated Winch, Plow & LED Mounts, Premium Cut & Sew Seats with Contoured Seatbacks and Embroidered Polaris Branding, Polaris HD 4500 lb. Synthetic Rope Winch with Autostop and Wireless Remote, Factory-Installed Poly Sport Roof, Single Latch Cab Nets, Polaris Pulse Electrical System (6 position), 12V Accessory Outlet, Battery Trickle-Charging Outlet, USB Outlet
- RIDE COMMAND+ Available as Accessory
- Tilt Steering: Standard

Tires / Wheels

- Front Tires: 29 x 9-14; PRO ARMOR X-TERRAIN
- Rear Tires: 29 x 11-14; PRO ARMOR X-TERRAIN
- Tire Ply Rating: 8-Ply Rated
- Wheels: Aluminum

Suspension

- Front: Suspension Dual A-Arm, 10 in (25.4 cm)
- Rear: Suspension Dual A-Arm IRS, 10 in (25.4 cm)
- Minimum Turning Radius: 13 ft. (4.0 m)

Doors

- Manual Crank Window Doors, Front, Poly, Set of 2

Windshield

- Lock & Ride® Full Windshield Vented, Hard Coat Poly

Rear Panel

- Lock & Ride® Rear Panel, Poly, Clear

Cab Heaters

- 8-Vent Heater & Defrost System

Delivery Address

Lake Ouachita State Park
5451 Mountain Pine Road
Mountain Pine, AR 71956

BRAND and MODEL BID: _____

BID PRICING: Including all delivery fees (DO NOT INCLUDE SALES TAX) (LIST PRICING EVEN IF ATTACHING QUOTE)

\$ _____ **Each (Quantity of 1)**

ADPHT-26-014 MINIMUM SPECIFICATIONS ATTACHMENT 3

Polaris Pro XD Full Size Diesel Crew Minimum Specifications (or equivalent see Section 3.3 C).

Engine & Drivetrain

- Air Intake: Front Air Intake with Donaldson® Cyclonic Air Filter
- Cooling: Liquid
- Cylinders Minimum Displacement: 898 cc
- Drive System Type: On-Demand 4x4
- Engine Type: 3-Cylinder Kubota® Diesel
- Fuel System/Battery: Mechanical Injection
- Minimum Horsepower: 23.3 HP
- Maintenance Interval: 200 Hours (50 Hour initial)
- Minimum Top Speed: 26 mph (41 km/h) *Adjustable with accessories
- Transmission/Final Drive: Automatic PVT H/L/N/R/P; Shaft

Dimensions

- Bed Box Dimensions: (L x W x H) 43.5 x 54 x 11.5 in (110.5 x 137 x 29 cm)
- Minimum Box Capacity: 1,250 lb. (567 kg)
- Estimated Dry Weight: 1,944 lb. (882 kg)
- Minimum Fuel Capacity: 11.5 gal (43.5 L)
- Minimum Ground Clearance: 11 in (27.9 cm)
- GVWR: 4,000 lb. (1,814 kg)
- Hitch Towing Rating: 2,500 lb. (1,134 kg)
- Overall Vehicle Size: (L x W x H) 157 x 62.5 x 75 in (399 x 159 x 191 cm)
- Minimum Payload Capacity: 1,900 lb. (862 kg)
- Minimum Person Capacity: 4
- Minimum Turning Radius: 207 in (525 cm)
- Minimum Wheelbase: 117 in (297.2 cm)

Brakes

- Front/Rear Brakes: 4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
- Parking Brake: Park in-transmission + Separate Mechanical Parking Brake Standard

Additional Specifications

- Cargo System: Lock & Ride®
- Preferred Color / Graphics: Gray
- Hitch Type: Standard 2 in (5 cm) Receiver
- Instrumentation: All Digital Gauge, Speedometer, Odometer, Tachometer, 2 Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, Engine Temperature, Hi-Temp Light, Clock, Clutch Belt Slip Warning, Glow Plug Indicator, Low Oil Pressure Indicator, Seat Belt Indicator, Parking Brake Engaged Alarm
- Lighting: 55W low/ 60W high, LED Tail

ADPHT-26-014

- Other Standard Features: Horn, Backup Alarm, Mechanically Controlled Speed Limiting
- Seat Covering: Kevlar®-Backed Vinyl (Grey)
- Tilt Steering: Standard

Tires/Wheels

- Electronic Power Steering: Standard
- Front Tires: 26 x 10-12 Duro® DI-2042 Power Grip (M/T)
- Hubs: Front: Steel; Rear: Ductile Iron
- Rear Tires: 26 x 10-12 Duro® DI-2042 Power Grip (M/T)
- Wheels: 12 x 6 HD Steel - Black

Suspension

- Front Suspension: 9 in (22.9 cm)
- Rear Suspension: 9 in (22.9 cm)

Delivery Address

Mount Magazine State Park
16878 Hwy 309 South
Paris, AR 72855

BRAND and MODEL BID: _____

BID PRICING: Including all delivery fees (DO NOT INCLUDE SALES TAX) (LIST PRICING EVEN IF ATTACHING QUOTE)

\$ _____ Each (Quantity of 1)

ADPHT-26-014 MINIMUM SPECIFICATIONS ATTACHMENT 4

Polaris Pro XD Full Size Diesel Crew Minimum Specifications (or equivalent see Section 3.3 C.)

Engine & Drivetrain

- Air Intake: Front Air Intake with Donaldson® Cyclonic Air Filter
- Cooling: Liquid
- Cylinders Minimum Displacement: 898 cc
- Drive System Type: On-Demand 4x4
- Engine Type: 3-Cylinder Kubota® Diesel
- Fuel System/Battery: Mechanical Injection
- Minimum Horsepower: 23.3 HP
- Maintenance Interval: 200 Hours (50 Hour initial)
- Minimum Top Speed: 26 mph (41 km/h)
- Transmission/Final Drive: Automatic PVT H/L/N/R/P; Shaft

Dimensions

- Bed Box Dimensions: (L x W x H) 43.5 x 54 x 11.5 in (110.5 x 137 x 29 cm)
- Minimum Box Capacity: 1,250 lb. (567 kg)
- Estimated Dry Weight: 1,944 lb. (882 kg)
- Minimum Fuel Capacity: 11.5 gal (43.5 L)
- Minimum Ground Clearance: 11 in (27.9 cm)
- GVWR: 4,000 lb. (1,814 kg)
- Hitch Towing Rating: 2,500 lb. (1,134 kg)
- Overall Vehicle Size: (L x W x H) 157 x 62.5 x 75 in (399 x 159 x 191 cm)
- Minimum Payload Capacity: 1,900 lb. (862 kg)
- Minimum Person Capacity: 4
- Minimum Turning Radius: 207 in (525 cm)
- Minimum Wheelbase: 117 in (297.2 cm)

Brakes

- Front/Rear Brakes: 4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
- Parking Brake: Park in-transmission + Separate Mechanical Parking Brake Standard

Additional Specifications

- Cargo System: Lock & Ride®
- Preferred Color / Graphics: Grey
- Hitch Type: Standard 2 in (5 cm) Receiver
- Instrumentation: All Digital Gauge, Speedometer, Odometer, Tachometer, 2 Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, Engine Temperature, Hi-Temp Light, Clock, Clutch Belt Slip Warning, Glow Plug Indicator, Low Oil Pressure Indicator, Seat Belt Indicator, Parking Brake Engaged Alarm
- Lighting: 55W low/ 60W high, LED Tail

ADPHT-26-014

- Other Standard Features: Horn, Backup Alarm, Mechanically Controlled Speed Limiting
- Seat Covering: Kevlar®-Backed Vinyl (Grey)
- Tilt Steering: Standard

Tires/Wheels

- Electronic Power Steering: Standard
- Front Tires: 26 x 10-12 Duro® DI-2042 Power Grip (M/T)
- Hubs: Front: Steel; Rear: Ductile Iron
- Rear Tires: 26 x 10-12 Duro® DI-2042 Power Grip (M/T)
- Wheels: 12 x 6 HD Steel - Black

Suspension

- Front Suspension: 9 in (22.9 cm)
- Rear Suspension: 9 in (22.9 cm)

Delivery Address

Mount Magazine State Park
16878 Hwy 309 South
Paris, AR 72855

BRAND and MODEL BID: _____

PRICING: Including all delivery fees (DO NOT INCLUDE SALES TAX) (LIST PRICING EVEN IF ATTACHING QUOTE)

\$ _____ Each (Quantity of 1)

ADPHT-26-014 MINIMUM SPECIFICATIONS ATTACHMENT 5

Polaris Ranger XP 1000 NorthStar Premium w/Fixed Windshield Minimum Specifications (or equivalent see Section 3.3 C.)

Engine and Drivetrain

- Cooling: Liquid
- Cylinders Minimum Displacement: 999cc
- Drive System Type: High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode
- Engine Type: ProStar 4-Stroke Twin Cylinder DOHC
- Fuel System/Battery: Electronic Fuel Injection
- Minimum Horsepower: 82 HP
- Transmission/Final Drive: Gen 2 Automatic PVT H/L/N/R/P; Shaft

Dimensions

- Bed Box Dimensions: (L x W x H) 36.75 x 54.25 x 12.5 in (93 x 138 x 32 cm)
- Minimum Box Capacity: 1000 lbs. (454 kg) California Models: 600 lbs. (272 kg)
- Estimated Dry Weight: 1,930 lb. (876 kg)
- Minimum Fuel Capacity: 11.5 gal (43.5 L)
- Minimum Ground Clearance: 14 in (36 cm)
- GVW 3,600 lbs. (1633 kg)
- Hitch Towing Rating: 2,500 lb. (1,134 kg)
- Hitch Type Standard: 2 in (5 cm) Receiver
- Overall Vehicle Size: (L x W x H) 120 x 65 x 79.5 in. (305 x 165 x 201 cm)
- Minimum Payload Capacity: 1,275 lbs. (578 kg) California Models: 1,100 lbs. (499 kg)
- Minimum Person Capacity: 3
- Water Fording Height: Equal to the Floorboards
- Minimum Wheelbase: 81 in (206 cm)

Brakes

- Front/Rear Brakes: 4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
- Parking Brake: Park in-transmission

Tires / Wheels

- Front Tires: 29 x 9-14; PRO ARMOR X-TERRAIN
- Rear Tires: 29 x 11-14; PRO ARMOR X-TERRAIN
- Tire Ply Rating: 8-Ply Rated
- Wheels: Aluminum

Additional Specifications

- Adjustable Driver Seat: Standard
- Cargo System: Lock & Ride®

- Preferred Color / Graphics: Green
- Electronic Power Steering High: Output EPS
- Instrumentation: Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, 2 DC Outlets, USB Charge Port
- Lighting: Dual LED Headlights, 1250lm Low Beam, 2300lm High Beam, Dual LED Taillights
- Other Standard Features: Premium Pro-Shield Cab; Doors with Crank Windows; Fixed Glass Windshield with Wiper; Rear Glass Panel; Factory-Installed Heat, AC, Defrost; Rearview Mirror; Premium Steering Wheel and Interior Accents; NorthStar Tailgate Badge; Front Bumper with Integrated Winch, Plow & LED Mounts; Premium Cut & Sew Seats with Contoured Seatbacks and Embroidered Polaris Branding; Polaris HD 4,500 lb. Synthetic Rope Winch with AutoStop and Wireless Remote; Polaris Pulse Electrical System (6-Position) Underhood Busbar and 6-Position Roof Busbar; 12V Accessory Outlet; Battery Trickle-Charging Outlet; USB Outlet
- Tilt Steering: Standard

Suspension

- Front Suspension: Dual A-Arm, 10 in (25.4 cm)
- Rear Suspension: Dual A-Arm IRS, 10 in (25.4 cm)
- Minimum Turning Radius: 13 ft. (4.0 m)

Windows

- Front Windshield: Fixed Glass with Wiper
- Rear Windshield: Glass Panel
- Door Windows: Crank (manual) Windows

Delivery Address

Petit Jean State Park
1285 Petit Jean Mountain Road
Morrilton, AR 72110

BRAND and MODEL BID: _____

PRICING: Including all delivery fees (DO NOT INCLUDE SALES TAX) (LIST PRICING EVEN IF ATTACHING QUOTE)

\$ _____ Each (Quantity of 1)

ADPHT-26-014 MINIMUM SPECIFICATIONS ATTACHMENT 6

Polaris Ranger Crew XP 1000 Premium Minimum Specifications

Engine and Drivetrain

- Cooling: Liquid
- Cylinders Minimum Displacement: 999 cc
- Drive System Type: Selectable on-demand all-wheel drive, AWD/2WD/VersaTrac Turf Mode
- Engine Type: 4-stroke twin cylinder DOHC
- Fuel System/Battery: Electronic fuel injection
- Minimum Horsepower: 82 HP
- Transmission/Final Drive: Gen 2 Automatic PVT H/L/N/R/P; shaft

Dimensions

- Bed Box Dimensions: (L x W x H) 36.7 x 54.2 x 12.5" (93 x 138 x 32 cm)
- Minimum Box Capacity: 1,000 lbs. (454 kg) California Models: 600 lbs. (272 kg)
- Estimated Dry Weight: 2,018 lbs. (915 kg)
- Minimum Fuel Capacity: 11.5 gal (43.5 L)
- Minimum Ground Clearance: 14" (36 cm)
- Hitch Type: Standard 2" (5 cm) receiver
- Overall Vehicle Size: (L x W x H) 152 x 62.5 x 79.5" (386 x 158 x 201 cm)
- Minimum Payload Capacity: 1,600 lbs. (726 kg) CA Models: 1,350 lbs. (612 kg)
- Minimum Person Capacity: 6
- Minimum Towing Capacity: 2,500 lbs. (1,134 kg)
- Minimum Turning Radius: 17.5 ft (5.3 m)
- Water Fording Height: Equal to the Floorboards
- Minimum Wheelbase: 113" (287 cm)

Brakes

- Front/Rear Brakes: 4-wheel hydraulic disc with dual-bore front and rear calipers
- Parking Brake: Park in-transmission

Additional Specifications

- Security: Polaris P.A.S.S. anti-theft system
- Cargo System: Gas-assist dump box with Lock & Ride accessory integration
- Preferred Color / Graphics: Red
- Door Type: Cab nets
- Vehicle Protection: Large steel bumper, full-coverage skid plate, A-arm guards
- Winch: 4,500-lbs. Winch with synthetic rope, Auto Stop and wireless remote
- Electrical System: 660-W charging system, Polaris Pulse electrical system (3-position), 12V accessory outlet, battery trickle-charging port
- Lighting: Dual LED headlights, 1,250-lm low beam, 2,300-lm high beam, dual LED taillights

- Cab Components: Roof
- Driver Instrumentation: Dual-sweep analog dials with 4" LCD rider information center: user selectable blue/red backlighting and brightness, passcode protection, programmable service intervals, speedometer, programmable speed limiting, tachometer, odometer, tripmeter, clock, hour meter, gear indicator, fuel gauge, coolant temperature, voltmeter, service indicator and codes, seat belt reminder
- Electronic Power Steering: High-output EPS
- Seat Type: 6-person, dual-row, bolstered bench seats with 3-point harness and adjustable driver seat
- Speed Limiting: Speed limiting controlled in gauge
- Steering: Tilt adjustment

Tires / Wheels

- Front Tires: 29 x 9-14; Pro Armor X Terrain
- Rear Tires: 29 x 11-14; Pro Armor X Terrain
- Tire Ply Rating: 8-ply
- Wheels: 14" aluminum

Suspension

- Front Suspension: Dual A-arm, 10" (25.4 cm) travel
- Rear Suspension: Dual A-arm, 10" (25.4 cm) travel

Delivery Address

Queen Wilhelmina State Park
3877 Highway 88 West
Mena, AR 71953

BRAND and MODEL BID: _____

BID PRICING: Including all delivery fees (DO NOT INCLUDE SALES TAX) (LIST PRICING EVEN IF ATTACHING QUOTE)

\$ _____ Each (Quantity of 1)